



Breitflanschträger HEA

S235JR - EN 10025 - Warmgewalzt

| Profil | Gewicht | Höhe h | Breite b | Steg tw | Flansch tf | Länge |
|------------|---------|--------|----------|---------|------------|-------|
| HEA | Kg/m | mm | mm | mm | mm | m |
| HEA - 100 | 16.70 | 96 | 100 | 5.00 | 8.00 | 18.1 |
| HEA - 120 | 19.90 | 114 | 120 | 5.00 | 8.00 | 18.1 |
| HEA - 140 | 24.70 | 133 | 140 | 5.50 | 8.50 | 18.1 |
| HEA - 160 | 30.40 | 152 | 160 | 6.00 | 9.00 | 18.1 |
| HEA - 180 | 35.50 | 171 | 180 | 6.00 | 9.50 | 18.1 |
| HEA - 200 | 42.30 | 190 | 200 | 6.50 | 10.00 | 18.1 |
| HEA - 220 | 50.50 | 210 | 220 | 7.00 | 11.00 | 18.1 |
| HEA - 240 | 60.30 | 230 | 240 | 7.50 | 12.00 | 18.1 |
| HEA - 260 | 68.20 | 250 | 260 | 7.50 | 12.50 | 18.1 |
| HEA - 280 | 76.40 | 270 | 280 | 8.00 | 13.00 | 18.1 |
| HEA - 300 | 88.30 | 290 | 300 | 8.50 | 14.00 | 18.1 |
| HEA - 320 | 97.60 | 310 | 300 | 9.00 | 15.50 | 18.1 |
| HEA - 340 | 105.00 | 330 | 300 | 9.50 | 16.50 | 18.1 |
| HEA - 360 | 112.00 | 350 | 300 | 10.00 | 17.50 | 18.1 |
| HEA - 400 | 125.00 | 390 | 300 | 11.00 | 19.00 | 18.1 |
| HEA - 450 | 140.00 | 440 | 300 | 11.50 | 21.00 | 18.1 |
| HEA - 500 | 155.00 | 490 | 300 | 12.00 | 23.00 | 18.1 |
| HEA - 550 | 166.00 | 540 | 300 | 12.50 | 24.00 | 18.1 |
| HEA - 600 | 178.00 | 590 | 300 | 13.00 | 25.00 | 18.1 |
| HEA - 650 | 190.00 | 640 | 300 | 13.50 | 26.00 | 18.1 |
| HEA - 700 | 204.00 | 690 | 300 | 14.50 | 27.00 | 18.1 |
| HEA - 800 | 224.00 | 790 | 300 | 15.00 | 28.00 | 18.1 |
| HEA - 900 | 252.00 | 890 | 300 | 16.00 | 30.00 | 18.1 |
| HEA - 1000 | 272.00 | 990 | 300 | 16.50 | 31.00 | 18.1 |