


Breitflanschträger HEM

S235JR - EN 10025 - Warmgewalzt



	Gewicht	Höhe h	Breite b	Steg tw	Flansch tf	Länge
HEM	Kg/m	mm	mm	mm	mm	m
HEM - 100	41.80	120	106	12.00	20.00	18.1
HEM - 120	52.10	140	126	12.50	21.00	18.1
HEM - 140	63.20	160	146	13.00	22.00	18.1
HEM - 160	76.20	180	166	14.00	23.00	18.1
HEM - 180	88.90	200	186	14.50	24.00	18.1
HEM - 200	103.00	220	206	15.00	25.00	18.1
HEM - 220	117.00	240	226	15.50	26.00	18.1
HEM - 240	157.00	270	248	18.00	32.00	18.1
HEM - 260	172.00	290	268	18.00	32.50	18.1
HEM - 280	189.00	310	288	18.50	33.00	18.1
HEM - 300	238.00	340	310	21.00	39.00	18.1
HEM - 320	245.00	359	309	21.00	40.00	18.1
HEM - 340	248.00	377	309	21.00	40.00	18.1
HEM - 360	250.00	395	308	21.00	40.00	18.1
HEM - 400	256.00	432	307	21.00	40.00	18.1
HEM - 450	263.00	478	307	21.00	40.00	18.1
HEM - 500	270.00	524	306	21.00	40.00	18.1
HEM - 550	278.00	572	306	21.00	40.00	18.1
HEM - 600	285.00	620	305	21.00	40.00	18.1
HEM - 650	293.00	668	305	21.00	40.00	18.1
HEM - 700	301.00	716	304	21.00	40.00	18.1
HEM - 800	317.00	814	303	21.00	40.00	18.1
HEM - 900	333.00	910	302	21.00	40.00	18.1
HEM - 1000	349.00	1008	302	21.00	40.00	18.1