



## INP - Träger

S355JO - EN 10025 - Warmgewalzt

Profil	Gewicht	Höhe h	Breite b	Steg tw	Flansch tf	Länge
INP	Kg/m	mm	mm	mm	mm	m
INP - 80	5.94	80	42	3.90	5.90	12.1
INP - 100	8.34	100	50	4.50	6.80	12.1
INP - 120	11.10	120	58	5.10	7.70	12.1
INP - 140	14.30	140	66	5.70	8.60	12.1
INP - 160	17.90	160	74	6.30	9.50	12.1
INP - 180	21.90	180	82	6.90	10.40	12.1
INP - 200	26.20	200	90	7.50	11.30	12.1
INP - 220	31.10	220	98	8.10	12.20	12.1
INP - 240	36.20	240	106	8.70	13.10	12.1
INP - 260	41.90	260	113	9.40	14.10	12.1
INP - 280	47.90	280	119	10.10	15.20	12.1
INP - 300	54.20	300	125	10.80	16.20	12.1
INP - 320	61.10	320	131	11.50	17.30	12.1
INP - 340	68.10	340	137	12.20	18.30	12.1
INP - 360	76.10	360	143	13.00	19.50	12.1
INP - 380	84.00	380	149	13.70	20.50	12.1
INP - 400	92.40	400	155	14.40	21.60	12.1
INP - 450	115.00	450	170	16.20	24.30	12.1
INP - 500	141.00	500	185	18.00	27.00	12.1