



UNP - Träger

S355JO - EN 10025 - Warmgewalzt

Profil	Gewicht	Höhe h	Breite b	Steg tw	Flansch tf	Länge
UNP	Kg/m	mm	mm	mm	mm	m
UNP - 80	8.64	80	45	6.00	8.00	12.1
UNP - 100	10.60	100	50	6.00	8.50	12.1
UNP - 120	13.40	120	55	7.00	9.00	12.1
UNP - 140	16.00	140	60	7.00	10.00	12.1
UNP - 160	18.80	160	65	7.50	10.50	18.1
UNP - 180	22.00	180	70	8.00	11.00	18.1
UNP - 200	25.30	200	75	8.50	11.50	18.1
UNP - 220	29.40	220	80	9.00	12.50	18.1
UNP - 240	33.20	240	85	9.50	13.00	18.1
UNP - 260	37.90	260	90	10.00	14.00	18.1
UNP - 280	41.80	280	95	10.00	15.00	18.1
UNP - 300	46.20	300	100	10.00	16.00	18.1
UNP - 320	59.50	320	100	14.00	17.50	18.1
UNP - 350	60.60	350	100	14.00	16.00	18.1
UNP - 380	63.10	380	102	13.50	16.00	18.1
UNP - 400	71.80	400	110	14.00	18.00	18.1