

LDPE KABELSCHUTZROHRE C+S GEMUFFT COEXTRUDIERT AUS REZYKLAT

Aussen weiss mit roten Markierungsstreifen, innen schwarz, Scheiteldruckfestigkeit grösser SN 4

Mit Dichtung und Muffendeckel



dn mm	Artikel- Nr.	e mm	D mm	C mm	A mm	L mm	Gewicht kg/m	Palette m
72/60	151.413.124	6.0	95.0	38.0	82.0	5000	1.300	490
72/60	151.417.124	6.0	95.0	38.0	82.0	10000	1.280	980
92/80	151.413.126	6.0	115.0	38.0	90.0	5000	1.700	300
92/80	151.417.126	6.0	115.0	38.0	90.0	10000	1.670	600
112/100	151.413.128	6.0	137.0	39.0	97.0	5000	2.100	225
112/100	151.417.128	6.0	137.0	39.0	97.0	10000	2.060	450
132/120	151.413.130	6.0	159.0	41.0	105.0	5000	2.510	140
132/120	151.417.130	6.0	159.0	41.0	105.0	10000	2.450	280
163/148	151.413.134	7.5	190.5	45.0	111.0	5000	3.900	90
163/148	151.417.134	7.5	190.5	45.0	111.0	10000	3.800	180
214/195	151.413.136	9.5	248.0	40.0	129.0	5000	6.570	40
214/195	151.417.136	9.5	248.0	40.0	129.0	10000	6.360	80