



IPE - Träger

S235JR - EN 10025 - Warmgewalzt

Profil	Gewicht	Höhe h	Breite b	Steg tw	Flansch tf	Länge
IPE	Kg/m	mm	mm	mm	mm	m
IPE - 80	6.00	80	46	3.80	5.20	12.1
IPE - 100	8.10	100	55	4.10	5.70	12.1
IPE - 120	10.40	120	64	4.40	6.30	12.1
IPE - 140	12.90	140	73	4.70	6.90	12.1
IPE - 160	15.80	160	82	5.00	7.40	12.1
IPE - 180	18.80	180	91	5.30	8.00	12.1
IPE - 200	22.40	200	100	5.60	8.50	18.1
IPE - 220	26.20	220	110	5.90	9.20	18.1
IPE - 240	30.70	240	120	6.20	9.80	18.1
IPE - 270	36.10	270	135	6.60	10.20	18.1
IPE - 300	42.20	300	150	7.10	10.70	18.1
IPE - 330	49.10	330	160	7.50	11.50	18.1
IPE - 360	57.10	360	170	8.00	12.70	18.1
IPE - 400	66.30	400	180	8.60	13.50	18.1
IPE - 450	77.60	450	190	9.40	14.60	18.1
IPE - 500	90.70	500	200	10.20	16.00	18.1
IPE - 550	106.00	550	210	11.10	17.20	18.1
IPE - 600	122.00	600	220	12.00	19.00	18.1