


**Flachstahl warmgewalzt**

S235JR - EN 10025




| Breite <b>b</b> | Höhe <b>h</b> | Gewicht |
|-----------------|---------------|---------|
| mm              | mm            | Kg/m    |

|       |   |      |
|-------|---|------|
| 10    | 3 | 0.23 |
| 15    | 3 | 0.35 |
| 20    | 3 | 0.47 |
| 25    | 3 | 0.58 |
| 30    | 3 | 0.70 |
| 35    | 3 | 0.82 |
| 40    | 3 | 0.94 |
| 50    | 3 | 1.18 |
| 60    | 3 | 1.41 |
| 70    | 3 | 1.65 |
| 80    | 3 | 1.88 |
| <hr/> |   |      |
| 10    | 4 | 0.31 |
| 15    | 4 | 0.47 |
| 20    | 4 | 0.62 |
| 25    | 4 | 0.78 |
| 30    | 4 | 0.94 |
| 35    | 4 | 1.10 |
| 40    | 4 | 1.26 |
| 45    | 4 | 1.41 |
| 50    | 4 | 1.57 |
| 60    | 4 | 1.88 |
| 70    | 4 | 2.20 |
| 80    | 4 | 2.51 |
| 90    | 4 | 2.83 |
| 100   | 4 | 3.14 |
| 120   | 4 | 3.77 |
| <hr/> |   |      |
| 10    | 5 | 0.39 |

| Breite <b>b</b> | Höhe <b>h</b> | Gewicht |
|-----------------|---------------|---------|
| mm              | mm            | Kg/m    |

|       |   |      |
|-------|---|------|
| 15    | 5 | 0.58 |
| 20    | 5 | 0.78 |
| 25    | 5 | 0.98 |
| 30    | 5 | 1.18 |
| 35    | 5 | 1.37 |
| 40    | 5 | 1.57 |
| 45    | 5 | 1.77 |
| 50    | 5 | 1.96 |
| 60    | 5 | 2.36 |
| 70    | 5 | 2.75 |
| 80    | 5 | 3.14 |
| 90    | 5 | 3.53 |
| 100   | 5 | 3.93 |
| 120   | 5 | 4.71 |
| 130   | 5 | 5.10 |
| 140   | 5 | 5.50 |
| 150   | 5 | 5.89 |
| <hr/> |   |      |
| 12    | 6 | 0.56 |
| 15    | 6 | 0.70 |
| 20    | 6 | 0.94 |
| 25    | 6 | 1.18 |
| 30    | 6 | 1.41 |
| 35    | 6 | 1.65 |
| 40    | 6 | 1.88 |
| 45    | 6 | 2.12 |
| 50    | 6 | 2.36 |
| 60    | 6 | 2.83 |

Stangenlänge ca. 6.1m



**Flachstahl warmgewalzt**

S235JR - EN 10025


| Breite <b>b</b> | Höhe <b>h</b> | Gewicht |
|-----------------|---------------|---------|
| mm              | mm            | Kg/m    |
| 70              | 6             | 3.30    |
| 80              | 6             | 3.77    |
| 90              | 6             | 4.24    |
| 100             | 6             | 4.71    |
| 110             | 6             | 5.18    |
| 120             | 6             | 5.65    |
| 130             | 6             | 6.12    |
| 140             | 6             | 6.59    |
| 150             | 6             | 7.07    |
| <hr/>           |               |         |
| 15              | 8             | 0.94    |
| 20              | 8             | 1.26    |
| 25              | 8             | 1.57    |
| 30              | 8             | 1.88    |
| 35              | 8             | 2.20    |
| 40              | 8             | 2.51    |
| 45              | 8             | 2.83    |
| 50              | 8             | 3.14    |
| 60              | 8             | 3.77    |
| 70              | 8             | 4.40    |
| 80              | 8             | 5.02    |
| 90              | 8             | 5.65    |
| 100             | 8             | 6.28    |
| 110             | 8             | 6.91    |
| 120             | 8             | 7.54    |
| 130             | 8             | 8.16    |
| 140             | 8             | 8.79    |
| 150             | 8             | 9.42    |

| Breite <b>b</b> | Höhe <b>h</b> | Gewicht |
|-----------------|---------------|---------|
| mm              | mm            | Kg/m    |
| 15              | 10            | 1.18    |
| 20              | 10            | 1.57    |
| 25              | 10            | 1.96    |
| 30              | 10            | 2.36    |
| 35              | 10            | 2.75    |
| 40              | 10            | 3.14    |
| 45              | 10            | 3.53    |
| 50              | 10            | 3.93    |
| 60              | 10            | 4.71    |
| 70              | 10            | 5.50    |
| 80              | 10            | 6.28    |
| 90              | 10            | 7.07    |
| 100             | 10            | 7.85    |
| 110             | 10            | 8.64    |
| 120             | 10            | 9.42    |
| 130             | 10            | 10.20   |
| 140             | 10            | 11.00   |
| 150             | 10            | 11.80   |
| <hr/>           |               |         |
| 20              | 12            | 1.88    |
| 25              | 12            | 2.36    |
| 30              | 12            | 2.83    |
| 35              | 12            | 3.30    |
| 40              | 12            | 3.77    |
| 45              | 12            | 4.24    |
| 50              | 12            | 4.71    |

Stangenlänge ca. 6.1m

**Flachstahl warmgewalzt**

S235JR - EN 10025




| Breite <b>b</b> | Höhe <b>h</b> | Gewicht |
|-----------------|---------------|---------|
| mm              | mm            | Kg/m    |

|       |    |       |
|-------|----|-------|
| 60    | 12 | 5.65  |
| 70    | 12 | 6.59  |
| 80    | 12 | 7.54  |
| 90    | 12 | 8.48  |
| 100   | 12 | 9.42  |
| 110   | 12 | 10.40 |
| 120   | 12 | 11.30 |
| 130   | 12 | 12.20 |
| 140   | 12 | 13.20 |
| 150   | 12 | 14.10 |
| <hr/> |    |       |
| 20    | 15 | 2.36  |
| 25    | 15 | 2.94  |
| 30    | 15 | 3.53  |
| 35    | 15 | 4.12  |
| 40    | 15 | 4.71  |
| 45    | 15 | 5.30  |
| 50    | 15 | 5.89  |
| 60    | 15 | 7.07  |
| 70    | 15 | 8.24  |
| 80    | 15 | 9.42  |
| 90    | 15 | 10.60 |
| 100   | 15 | 11.80 |
| 110   | 15 | 13.00 |
| 120   | 15 | 14.10 |
| 130   | 15 | 15.30 |
| 140   | 15 | 16.20 |
| 150   | 15 | 17.70 |

| Breite <b>b</b> | Höhe <b>h</b> | Gewicht |
|-----------------|---------------|---------|
| mm              | mm            | Kg/m    |

|       |    |       |
|-------|----|-------|
| 30    | 20 | 4.71  |
| 35    | 20 | 5.50  |
| 40    | 20 | 6.28  |
| 50    | 20 | 7.85  |
| 60    | 20 | 9.42  |
| 70    | 20 | 11.00 |
| 80    | 20 | 12.60 |
| 90    | 20 | 14.10 |
| 100   | 20 | 15.70 |
| 110   | 20 | 17.30 |
| 120   | 20 | 18.80 |
| 130   | 20 | 20.40 |
| 140   | 20 | 22.00 |
| 150   | 20 | 23.60 |
| <hr/> |    |       |
| 40    | 25 | 7.85  |
| 50    | 25 | 9.81  |
| 60    | 25 | 11.80 |
| 70    | 25 | 13.70 |
| 80    | 25 | 15.70 |
| 90    | 25 | 17.70 |
| 100   | 25 | 19.60 |
| 110   | 25 | 21.60 |
| 120   | 25 | 23.60 |
| 130   | 25 | 25.50 |
| 140   | 25 | 27.50 |
| 150   | 25 | 29.40 |

Stangenlänge ca. 6.1m



**Flachstahl warmgewalzt**

S235JR - EN 10025

| Breite <b>b</b> | Höhe <b>h</b> | Gewicht |
|-----------------|---------------|---------|
| mm              | mm            | Kg/m    |
| 40              | 30            | 9.42    |
| 50              | 30            | 11.80   |
| 60              | 30            | 14.10   |
| 70              | 30            | 16.50   |
| 80              | 30            | 18.80   |
| 90              | 30            | 21.20   |
| 100             | 30            | 23.60   |
| 120             | 30            | 28.30   |
| 130             | 30            | 30.60   |
| 140             | 30            | 33.00   |
| 150             | 30            | 35.30   |
| 50              | 40            | 15.70   |
| 60              | 40            | 18.80   |
| 70              | 40            | 22.00   |
| 80              | 40            | 25.10   |

| Breite <b>b</b> | Höhe <b>h</b> | Gewicht |
|-----------------|---------------|---------|
| mm              | mm            | Kg/m    |
| 90              | 40            | 28.30   |
| 100             | 40            | 31.40   |
| 120             | 40            | 37.70   |
| 130             | 40            | 40.80   |
| 140             | 40            | 44.00   |
| 150             | 40            | 40.80   |
| 70              | 50            | 27.50   |
| 80              | 50            | 31.40   |
| 100             | 50            | 39.30   |
| 120             | 50            | 47.10   |
| 150             | 50            | 58.90   |
| 80              | 60            | 37.70   |
| 90              | 60            | 42.40   |
| 100             | 60            | 47.10   |
| 120             | 60            | 56.50   |
| 150             | 60            | 70.60   |

Stangenlänge ca. 6.1m